

**TYPE: Mini G Clamp 400Amp**


This device is an addition to our Electricity Network Connection range of specialist clamps. The "Mini" Clamp can be configured to have a cable attached directly to the clamp (as in the picture above) or with a connector end to accept our Powersafe generator plugs.

Arms are available in long extended, short or right angled versions.

The Mini Clamps, as with all other Network clamps in our production are intended for Live Line connection. The insulation performance is tested at 10,000 Volts in accordance with specification IEC60900: 2004 "Live Line working hand tools for use up to 1,000 Volts AC OR 1,500 Volts DC.

The Mini clamp has a rating of 400Amp continuous and has a reduced head width compared to our standard 600 Amp G clamp. The head is 26mm wide as apposed to 44mm wide on the standard 600Amp clamp.



This allows the temporary clamp connections to be used on equipment bus bars, where space limitations rule out the existing 600Amp clamp.

**Features**

- Can facilitate cable up to 150mm<sup>2</sup> (Cable tail termination version) or 300mm<sup>2</sup> (connector termination version)
- Manufactured from High conductivity copper, electro tinned plated.
- Insulation tested and certified for Live Line connection
- Configurable for cable or connector connections
- Minimum space requirement
- Available as complete clamp or in component form

For Further Information: Tel: 01592 775995 Fax: 01592 775996

Email: [sales@p3connectors.com](mailto:sales@p3connectors.com)